



Neoprene Gasket

Sealing Tape For Four Bolt Connector and Round and Flat Oval Connections

Specifications

- Hazardous Ingredients: None. This material is not made from chemical components that are known to present possible carcinogenic, mutagenic or other chronic hazards
- Odor: negligible
- Density: 3.0 to 14.0 lbs. per cubic foot
- Percent, volatile by volume: 0
- Flash point: n/a
- Extinguishing media: Water spray, dry chemical, CO₂
- Special fire fighting procedures: self contained breathing apparatus
- Unusual fire and explosion hazards: Toxic fire/gas hazard includes hydrogen chloride, a pulmonary irritant
- Oil Resistance: E1/E2 ASTM D 1056 78
- 25% Compression Resistance (PSI): 4.0 to 4.5 ASTM D 1667
- 50% Compression Set, Max (%) 25.0 ASTM D 1056 78
- Linear Shrinkage, Max 24hrs @ 158°(%) 3.0
- Flammability (Burning rate, in/min MVS 302, Horizontal strip 4x141/2x1/2" 4
- Flammability UL94 V- (1/2" and above) PASS
- Flammability UL94HBF (1/8" and above) PASS
- Flammability-FAR 25.853 A (1/4" sample) FAR 25.853 B PASS
- Water Absorbtion, Max % 5 ASTM D 1667
- Cold Crack (180° bend), min 1/2" mandrel within 5 sec -40 MIL P 15280
- Thermal Conductivity, Max (BTU/in/hr/sq.ft.0°F) .30 ASTM C 177
- Tensile Strength, Min (psi) 90 ASTM D 412
- Elongation, Min(%) 175 ASTM D 412
- Durometer, Shore 00: 40+/-5
- Temperature range, High Continuous: 150°
- Temperature range, High Intermittent: 200°
- Flame Spread: 10 ASTM E 84
- Fuel Contribution: 0 ASTM E 84
- Smoke Density: 0 ASTM E 84



Size

- 5/16" x 3/4"

Packaging

- 750 ft. per box - 50ft. Rolls.- 15lbs. per box

W
C.L. WARD
& FAMILY INC.



1460 Delberts Drive
Monongahela, PA 15063
888.973.7600
www.clward.com