



SuperSpray

Premium quality, pressure sensitive adhesive for a quick permanent tack.

Specifications

- Pressure sensitive
- Methylene chloride based
- Green in color
- Service Temperature: -30° to 160°F
- Application Temperature: 60° to 90°F
- Storage Temperature: Below 120° F
- Flammability: None
- Flashpoint: None
- Freeze thaw: Does not apply
- Coverage: 4,000 sq.ft. to 4,600 sq.ft. (Depending on temperature, humidity, and thickness)
- Bonding time: 1 to 10 minutes (Depending on applicatoion rate)
- Shelf life: 1 year
- High solids content (25%)
- Easy application
- Exptremely quick tack
- Strong permanent bond
- Meets DOT 39 NRC
- Non-Flammable in wet and dry state
- Exceptional coverage



Directions

Surfaces should be free from all dirt, oil, and grease.

Keep cylinder off of concrete floor during freezing temperatures. For best results use at temperatures between 60° to 90°F.

1. Make sure all surfaces to be sprayed are clean and free from debris, dust, dirt, grease, etc.
2. Try gun on a test surface to make sure adhesive is flowing.
3. Hold spray gun 8-10 inches from surface to be sprayed.
4. Avoid buildup of adhesive or buubles. Edges of spray pattern should overlap giving consistent coverage over surface.

For Permanent Bond: Spray both surfaces. Allow solvent to evaporate for 2 minutes before making the bond. Apply pressure to the bond. A hand roller or a pinch roller is most effective.

For Temporary Bond: Spray one surface. Allow to tack for 2 minutes.

Packaging

- SuperSpray 12 12 lbs
- SuperSpray 40 40 lbs

Accessory Equipment

- SuperSpray Gun
- SuperSpray 6' Hose
- SuerSpray 12' Hose
- SuerSpray 18' Hose

W
C.L. WARD
& FAMILY INC.



1460 Delberts Drive
Monongahela, PA 15063
888.973.7600
www.clward.com