

SpiralFlange

CONTACT

Office: 888.973.7600

1100 Ashwood Drive
Suite 1102
Canonsburg, PA 15317

www.clward.com

Detail


- Round duct connection system
- Meets SMACNA B Reinforcement Class
- 8" - 48" 18 gauge
50" and up - 16 gauge
- Available in galvanized, galvaneal, stainless, aluminum, aluminized and PVC
- Pre-Punched holes for easier duct connections (12" and up)
- No special tools required
- Available for 1" and 2" double wall
- Specially designed with a split to accommodate minor deviations of pipe diameter (also available welded)
- Available in "halves" for flat oval
- Straight material available for flat oval




Profile

- Available in 8" to 72"


In accordance with SMACNA Duct Performance Test Standards #DPTS-2005 as described in the HVAC Duct Construction Standards, Third Ed.-2005, the CL WARD & Family Inc. SpiralFlange for round duct connection system and round duct reinforcement meets the requirements of a SMACNA B Reinforcement Class.



1" Double Wall Profile



2" Double Wall Profile



Packaging

- Sold as single units

Item Code	Item Description	Packaging
EFRXGA	SpiralFlange - SPLIT	Per Order
EFRWXGA	SpiralFlange - WELDED	Per Order

X = Diameter

1" Double Wall, X = 2826 (outer/inner)

2" Double Wall, X = 2824 (outer/inner)