

# D-Galv



## CONTACT

1100 Ashwood Drive  
Suite 1102  
Canonsburg, PA 15317

[www.clward.com](http://www.clward.com)  
888.973.7600

[info@clward.com](mailto:info@clward.com)

## DETAIL

D-Galv is a combination de-galvanizing and lubricant spray to keep sheet metal machinery free from galvanizing build-up while at the same time providing lubrication to the machinery to ensure consistent operation and fabrication.

## FEATURES

- Easy to see color
- Great lubricant
- Cleans and protects
- Removes galvanizing build-up
- Consistant spray pattern
- Safe for all metal forming equipment



## TECHNICAL

- Color: Red
- Base: Solvent
- Viscosity: 21 cps
- Spray Force: .021 lbf
- Density: 7.18 lb/gal

To properly apply D-Galv, first ensure the can has been shaken. In a well ventilated area, with the tip pointing away from yourself and others, press the top of the spray nozzle to release the material from the can. When you locate a point of galvanized build-up, or a point of lubrication, spray the point keeping the tip 8 to 12 inches away from the component to be sprayed.

To ensure full disposal of the can, it's best to spray at a 90 degree angle to the component.

## PACKAGING

ITEM CODE	ITEM DESCRIPTION	PACKAGING	WEIGHT
DGALVSPRAY	CL WARD D-Galv Spray - 11 oz can	12 cans/case	54 lbs/case

Proud members of the following organizations:

