

FiberCoat™

CONTACT

Office: 888.973.7600

1100 Ashwood Drive
Suite 1102
Canonsburg, PA 15317
Can

www.clward.com

Detail

Aerosol edge coating spray to protect and repair fiberglass insulation.

- Propellant: Aerosol
- Color: Black
- Solids: 26-31%
- Odor: Light
- Application Temp: 60-100°F
- Storage Temp: Approximately 72°F
- Spray Force: Strong spray force - > .90 ozF
- Coverage: 50 sq.ft. per can
- Flammability: Flammable (only in wet state)
- Shelf Life: Approximately 1 year
- High Strength and durability
- Quick drying
- Tack-free after curing
- Remains flexible
- Encapsulate cut or damaged insulation
- VOC Content: 28%
- TVOC Emissions: CDPH Standard Method v 1.2
Private Office - Pass
School Classroom - Pass



Packaging

Item	Description	Packaging	Weight
FIBERCOAT	FiberCoat 13 oz. Can	12 cans/case	13 lbs/case

Application

Shake well before each use. Hold spray can approximately 5" from the surface to be sprayed. Apply to the edge of the duct insulation or to any cut/tears that need to be encapsulated to prevent fibers from entering the air stream.

Do not use or store near open flame or any source of heat.