

S-Seal Spray

Qualifies for LEED Credit EQ 4.1

Detail

Premium grade water based **"SPRAYABLE"** duct sealant.

- Fire Resistant
- UL 723 Classification
- UL 181B-M Listed
- Conforms to Requirements of NFPA 90A and 90B
- Manufactured by SMART Local #12
- Tested to 15" w.g.
- Extremely Flexible
- Water Based
- Resists Mildew
- Base: Synthetic latex emulsion
- Color: Gray
- Type: Water Base
- Weight: 11±.2 lbs per gallon
- Solid Contents: 66% ±2%
- Viscosity: 80,000 c.p.s.
- Application Temp: 35°F to 100°F
- Service Temp: -25°F to 175°F
- Storage Temp: 40°F to 85°F
- Dry To Touch: 1 hour (approx.)
- Cure Time: 24 to 72 hours + (depending on humidity, application, and temperature)
- Flammability: Non-flammable in both wet and dry state
- Flash Point: No flash to boiling
- Mildew Resistance: Excellent
- Water Resistance: Excellent
- Flexibility: Excellent
- Freeze Thaw Stability: 5 cycles
- Coverage: 25 sq.ft./gal. at 1/16" 50 sq.ft./gal. at 1/32"
- Odor: Mild (wet) None (dry)
- Shelf Life: 1 year
- Cured Sealant: Tough and permanently flexible
- Flame Spread: 0
- Smoke Developed: 0
- Ultraviolet Ray and Ozone resistant
- LEED Compliant



CONTACT

Office: 888.973.7600

1100 Ashwood Drive
Suite 1102
Canonsburg, PA 15317

www.clward.com

Packaging

Item	Description	Packaging	Weight
SSEALSPRAY5	S-Seal Spray 5 gal	each	64 lbs/pail