

SuperSpray

Qualifies for LEED Credit EQ 4.1

Detail

A nonflammable duct liner adhesive that provides a strong hold with quick dry time. SuperSpray is suitable for all types of HVAC insulations such as elastomeric, fiberglass, polyester and even substrates like plywood.

- Color: Light Yellow to Clear
- Spray Pattern: Web
- Tack: Extremely Aggressive Wet Tack, Permanent dry tack
- Flammability: Non-flammable
- Propellant: Methylene Chloride
- Coverage: $\geq 4,000$ sq.ft per Canister
- VOC's: 0 g/L
- Low odor
- Solid Content: 29-35%
- Application Temperature: 60-100°F
- Maximum Storage Temperature: 120°F
- Dry Time: 2-4 minutes
- 7L and 22L are disposable/recyclable containers
- 180L and 216L are custom ordered and returnable containers
- Shelf Life: 18 months
- Less weight per canister than competing brands



CONTACT

Office: 888.973.7600

1100 Ashwood Drive
Suite 1102
Canonsburg, PA 15317

www.clward.com

Packaging

| Item | Description | Packaging | Weight |
|---------------|--------------------------|-----------|---------|
| SUPERSPRAY7 | SuperSpray 7L Canister | Each | 8 lbs |
| SUPERSPRAY22 | SuperSpray 22L Canister | Each | 33 lbs |
| SUPERSPRAY108 | SuperSpray 108L Canister | Each | 152 lbs |
| SUPERSPRAY216 | SuperSpray 216L Canister | Each | 303 lbs |
| SSH6 | SuperSpray Hose 6 ft | Each | 2 lbs |
| SSH8 | SuperSpray Hose 8 ft | Each | 5 lbs |
| SSH12 | SuperSpray Hose 12 ft | Each | 4 lbs |
| SSH18 | SuperSpray Hose 18 ft | Each | 6 lbs |
| SSG | SuperSpray Gun | Each | 4 lbs |