

SPEEDYSHOT 3

The SpeedyShot 3 can be used on the CL WARD J Flange, H Flange and SpiralFlange (round connector). This is our lightest fastening gun to date. The fully automatic operation greatly reduces fastening time by inserting a fastener at one per second. The fasteners come 200 to a coil, eliminating the need to reload a tek screw each time you need to install a fastener....resulting in reduced labor time.

Because of the automatic operation and the light weight of the gun, worker fatigue is reduced as well!

Incorporating the SpeedyShot 3 in your shop is a great way to streamline your duct fabrication to save time and money!



GUN

- Weight - 10.5 lbs
- Recommended Operating Pressure - 80 to 120 p.s.i.
- Air Consumption - Approx 2 c.f.m. at 110 p.s.i.
- Noise - 94 dB sound power level
- Tool uses 1/4" N.P.T. male plug
- Power Source - Clean, regulated compressed air
- Clamping mechanism to ensure accurate fastening
- Inserts fastener in a fraction of a second

Fasteners

- Item code - SS3000 (200 per coil, 3,000 per box)
- Coil-collated steel pins for steel to steel connections
- Fastener Length - 3/4" (19mm)
- Shank Diameter - .100" (2.5mm)
- Shank Type - Helical, GripShank®